

## CIRCUIT BREAKER DATA

Luminaire Family:	<b>CIRKEL Downlight</b>
Sub-families:	<b>Square, Round, Wallwasher</b>
Applicable Model Range:	<b>All 8W/850lm DALI variants</b>

Inrush Current and Maximum Loading of Automatic Circuit Breakers (MCB):										
Circuit Breaker Type	C10	C13	C16	C20	B10	B13	B16	B20	Inrush Current	
Wire cross section	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	4mm <sup>2</sup>	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	4mm <sup>2</sup>	I <sub>max</sub>	Time (*)
Max # of Fittings per MCB	40	56	64	80	24	31	38	48	16A	255µs

(\*): Defined as the duration between 10% of peak (ascending) and 50% of peak (descending).

### IMPORTANT:

- The above are maximum quantities calculated based on the inrush current and provided as a guide only.
- DO NOT exceed the maximum rated continuous current of the circuit breaker.
- Calculation uses typical values from ABB series S200 as a reference.
- Information about the tripping characteristics of a specific circuit breaker must be requested from the circuit breaker manufacturer!
- Actual values may differ depending on the specific circuit breaker type(s) used and the installation environment such as the cable size, length, safety buffer, etc.

## CIRKEL BREAKER DATA

Luminaire Family:	<b>CIRKEL Downlight</b>
Sub-families:	<b>Square, Round, Wallwasher</b>
Applicable Model Range:	<b>All 8W/850lm Non-Dim variants</b>

Inrush Current and Maximum Loading of Automatic Circuit Breakers (MCB):										
Circuit Breaker Type	C10	C13	C16	C20	B10	B13	B16	B20	Inrush Current	
Wire cross section	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	2.5mm <sup>2</sup>	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	2.5mm <sup>2</sup>	I <sub>max</sub>	Time (*)
Max # of Fittings per MCB	21	28	36	45	13	17	22	27	22.4A	176µs

(\*): Defined as the duration between 10% of peak (ascending) and 50% of peak (descending).

### IMPORTANT:

- The above are maximum quantities calculated based on the inrush current and provided as a guide only.
- DO NOT exceed the maximum rated continuous current of the circuit breaker.
- Calculation uses typical values from ABB series S200 as a reference.
- Information about the tripping characteristics of a specific circuit breaker must be requested from the circuit breaker manufacturer!
- Actual values may differ depending on the specific circuit breaker type(s) used and the installation environment such as the cable size, length, safety buffer, etc.

## CIRKEL BREAKER DATA

Luminaire Family:	<b>CIRKEL Downlight</b>
Sub-families:	<b>Square, Round, Wallwasher</b>
Applicable Model Range:	<b>All 15W/1450lm DALI variants</b>

Inrush Current and Maximum Loading of Automatic Circuit Breakers (MCB):										
Circuit Breaker Type	C10	C13	C16	C20	B10	B13	B16	B20	Inrush Current	
Wire cross section	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	4mm <sup>2</sup>	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	4mm <sup>2</sup>	I <sub>max</sub>	Time (*)
Max # of Fittings per MCB	40	56	64	80	21	28	35	44	20A	140μs

(\*): Defined as the duration between 10% of peak (ascending) and 50% of peak (descending).

### IMPORTANT:

- The above are maximum quantities calculated based on the inrush current and provided as a guide only.
- DO NOT exceed the maximum rated continuous current of the circuit breaker.
- Calculation uses typical values from ABB series S200 as a reference.
- Information about the tripping characteristics of a specific circuit breaker must be requested from the circuit breaker manufacturer!
- Actual values may differ depending on the specific circuit breaker type(s) used and the installation environment such as the cable size, length, safety buffer, etc.

## CIRCUIT BREAKER DATA

Luminaire Family:	<b>CIRKEL Downlight</b>
Sub-families:	<b>Square, Round, Wallwasher</b>
Applicable Model Range:	<b>All 15W/1450lm Non-Dim variants</b>

<b>Inrush Current and Maximum Loading of Automatic Circuit Breakers (MCB):</b>										
<b>Circuit Breaker Type</b>	<b>C10</b>	<b>C13</b>	<b>C16</b>	<b>C20</b>	<b>B10</b>	<b>B13</b>	<b>B16</b>	<b>B20</b>	<b>Inrush Current</b>	
<b>Wire cross section</b>	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	<i>I</i> <sub>max</sub>	Time (*)
<b>Max # of Fittings per MCB</b>	52	67	85	104	32	41	50	62	14.5A	114µs

(\*): Defined as the duration between 10% of peak (ascending) and 50% of peak (descending).

### IMPORTANT:

- The above are maximum quantities calculated based on the inrush current and provided as a guide only.
- DO NOT exceed the maximum rated continuous current of the circuit breaker.
- Calculation uses typical values from ABB series S200 as a reference.
- Information about the tripping characteristics of a specific circuit breaker must be requested from the circuit breaker manufacturer!
- Actual values may differ depending on the specific circuit breaker type(s) used and the installation environment such as the cable size, length, safety buffer, etc.