


# OmniPOD


Optimising LED lighting technology




The OmniPOD range

**POD design** Optimal performance **Smart lighting** 10-year warranty\*  
**Versatile** 26% more Energy Efficient\*\* **Customisable** Made in Australia


OMNIPOD  
PENDANT




OMNIPOD RECESSED  
- LINEAR



OMNIPOD RECESSED  
- SQUARE



OMNIPOD  
DOWNLIGHT



DESIGNED  
TESTED  
MANUFACTURED


\*Applies to OmniPOD products with smart controls (e.g. Organic Response), and DALI. Excludes emergency and fixed output.\*\* All recessed OmniPODs are a minimum 26% more efficient than the previous generation.

# The OmniPOD brilliance



**THE POD**


The POD design creates the perfect downward light while the complementary diffuser illuminates the space. Together they deliver the unique OmniPOD effect.



POD

DIFFUSER

## POD + DIFFUSER





## OmniPOD range

The updated OmniPOD range features the latest LED technology and delivers an impressive 26%\* greater efficacy, significantly reducing electricity consumption. This translates to substantial cost savings and contributes to a greener planet. In addition to the efficiency gains, the OmniPOD range meets human-centric lighting standards by featuring low glare (UGR), CRI 90+ as standard, and optimised wide beam distribution – up to 3.2m spacing\*\*.

OmniPOD range now delivers an impressive 26%\* greater energy efficiency, significantly reducing electricity consumption.

### Energy Efficiency

	Efficacy
OmniPOD Pendant	144 lm/W
OmniPOD Recessed - Linear	140 lm/W
OmniPOD Recessed - Square	138 lm/W
OmniPOD Downlight	113 lm/W

\*All recessed OmniPODs are a minimum 26% more efficient than the previous generation. OmniPOD Downlight is 26% more efficient than previous model.  
\*\* Based on a 2.7m ceiling height.



# New OmniPOD pendant



## Customise with colour



### OmniPOD Pendant

Available in your choice of colour, offering endless possibilities. Seamlessly blend with the ceiling, introduce a bold contrast, or feature corporate brand colour





# Customise to suit your project

**WIPEDOWN**  
for hygiene  
applications such  
as medical and  
kitchen spaces.




**AIR SLOTS**  
allow additional room  
air circulation. OmniPOD  
products fit all air  
boot sizes.

Integrate **SMART  
LIGHTING** to achieve  
maximum energy  
efficiency. Connect  
Organic Response  
and control via a  
smartphone or  
tablet.



**MIX N MATCH –**  
POD and frame colours are  
interchangeable in – White/  
White, Black/Black, White/  
Black, Black/White.

**CUSTOM  
LENGTHS + SIZES**  
mean you can fit  
an OmniPOD into  
all applications e.g.  
Pendants available  
up to 2400mm in  
length.






# Customise your colour temperature

## TUNEABLE WHITE

Add Tuneable White to provide flexibility



## TUNEABLE DUO<sup>1</sup>

The inner (POD) and outer (Diffuser) operate as one. Fully adjustable from 2700-6500K, CRI 90+.

## TUNEABLE DUO<sup>2</sup>

The inner (POD) and outer (Diffuser) operate independently. Each fully adjustable from 2700-6500K, CRI 90+.

## FIXED CCT

All fixed CCT OmniPODs come in either 3000K or 4000K as standard.

# Organic Response smart lighting


## A SMART WAY TO REACH SUSTAINABILITY TARGETS

Organic Response is a flexible and innovative wireless 'plug & play' lighting control system that perfectly complements the OmniPOD range. Allowing each individual luminaire to make lighting decisions based on the presence of occupants in its immediate vicinity, ambient light levels, and information it receives from its neighbouring luminaires., Organic Response reduces energy consumption by up to 40%.







## CERTIFICATIONS

OmniPOD products with Organic Response will significantly contribute to your project achieving certifications such as a Green Star rating, NABERS, WELL, ISO 50001 EnMS, and Passivhaus.

Once installed, Organic Response reduces energy consumption by up to 40%



# OmniPOD Specification Guide

		Body Colour	POD Colour Options	Nominal Size [mm]			Max Target Spacing @ E <sub>h</sub> =320lux	Lighting Type Options		Controls			Emergency Option <sup>(2)</sup>	CLO Lifetime (L100B50) <sup>(3)</sup>	CRI/ R9	IP Rating <sup>(4)</sup>	Efficacy [lm/W]	UGR	CCT	Wipedown Film	Mounting Options <sup>(6)</sup>	Air Handling
				Length	Width	Height		Direct	Direct+ Indirect	OR	DALI	Other <sup>(1)</sup>										
Pendant	 OmniPOD Pendant	White, Black, Custom colours available	White / Black	1200, 1500, 2400	150	70	-	Y	Y	Y	Y*	Y*	N	50,000	90+/50	IP40 or IP44 <sup>(5)</sup>	144	16	4000K, 3000K, Tuneable White DUO <sup>1</sup> / DUO <sup>2</sup>	Y*	Suspended	N
Linear	 OmniPOD Linear			600, 1200,1500	300	38	2.4m x 3.2m		N	Y*	Y		Y*				140	19			T-Bar, PC, SM	Y*
	 OmniPOD 150			600, 1200, 1500	150	38	2.4m x 3.0m		N	Y	Y		Y*				140	19			T-Bar, PC, SM	N
Square	 OmniPOD 6x6 square			600	600	38	2.4m x 2.4m		N	Y	Y		Y*				138	19			T-Bar, PC, SM	Y*
	 OmniPOD 6x6 2-row			600	600	38	2.4m x 2.4m		N	Y	Y		Y*				138	16			T-Bar, PC, SM	Y*
Downlight	 OmniPOD Downlight			300	100	38	-		N	Y	Y		N				113	19			T-Bar, PC, SM	N

KEY - Y: Standard Y\*: Option N: Not Available

NOTES: 1. Other control options, including non-dim, are available. 2. Maintained DALI monitored, Maintained Non-monitored, and custom options are available. 3. The Constant Light Output (CLO) feature ensures no lumen depreciation until the luminaire reaches its L100B50 lifetime (cumulative usage hours). 4. Luminaires with an Organic Response node are rated IP20 from the room side, regardless of the original IP rating. 5. With Wipedown option. Wipedown layer provides IP44 from the room side in Linear, Square and Downlight variants with a ceiling side of IP40. Pendant with wipedown is rated IP44 from all directions. 6. Kits sold separately



eaglelighting.com.au  
info@eaglelighting.com.au  
Contact us today

**AUSTRALIA**

Victoria Head Office 17-19 Jets Court Melbourne Airport 3045 (03) 9344 7444	New South Wales Level 1 71-73 Alexander Street, Crows Nest 2065 (02) 9420 5799	Queensland 53 Caswell Street East Brisbane QLD 4169 (07) 3891 0744	Australian Capital Territory 0411 889 406
Western Australian (Distributor) H.I. Lighting 111 Broadway Bassendean WA 6054 (08) 9377 1322	South Australia (Distributor) Buckford Illumination Group, Unit 3, 169 Goodwood Road Millswood SA 5034 0448 064 412	Tasmania (Distributor) Southern Lighting 34 Federal Street North Hobart TAS 7000 (03) 6231 5599	

**NEW ZEALAND**

Auckland Citigroup Centre, 23 Custom St East Auckland Central 1010 New Zealand 0800 324 374	Lower North Island Wellington 021 597 900
--	---



A Fagerhult Group Company